

2024 Bridge City Battle Rules

Touring Stock by Janzen Hotrods:

Chassis: Any 1/10 scale 190mm 4WD touring car chassis

Motor: ROAR approved 21.5T

ESC: ROAR approved, must be run in blinky mode only.

Battery: 2S hardcase. Max voltage 8.400V

Weight: 1320g min

Ride Height: 5mm min

Bodies: Any ROAR/EFRA 190mm touring car body

Tires: Gravity Type C, Jaco blue, Sweep QTS 32 (blue or black). Bring your own

Race Length: 5min

USGT by RAD Racing & Development:

Chassis: Any 1/10 scale 190mm 4WD touring car chassis

Motor: ROAR approved 21.5T

ESC: ROAR approved, must be run in blinky mode only.

Battery: 2S hardcase. Max voltage 8.400V

Weight: 1350g min

Ride Height: 5mm min

Bodies: USGT/Scale type bodies only. No touring car bodies. Spoilers limited to 10mm height.

Tires: Gravity/Ride USGT tires/inserts only, belted or non-belted

Race Length: 5min

Touring Modified:

Chassis: Any 1/10 scale 190mm 4WD touring car chassis

Motor: Open

ESC: Open. Turbo/boost allowed

Battery: 2S hardcase. Max voltage 8.400V

Weight: 1320g min

Ride Height: 5mm min

Bodies: Any ROAR/EFRA 190mm touring car body

Tires: Gravity Type C, Jaco blue, Sweep QTS 32 (blue or black). Bring your own

Race Length: 5min

1/12 Stock:

Chassis: Any 1/12 scale 2wd pan car style chassis. 3D printed "Club Race Hero" style chassis also allowed

Motor: ROAR approved 17.5T

ESC: ROAR approved, must be run in blinky mode only.

Battery: 1S hardcase. Max voltage 4.200V

Weight: 730g min

Ride Height: 3mm min

Bodies: 1/12 LMP style

Tires: Purple/blue stripe 1/12 "spec" tires. Bring your own

Race Length: 8min

FWD Touring:

Chassis: Any 1/10 scale 190mm FWD touring car chassis

Motor: ROAR approved 21.5T

Gearing: Open

ESC: ROAR approved, must be run in blinky mode only.

Battery: 2S hardcase. Max voltage 8.400V

Weight: 1250g min

Ride Height: 5mm min

Bodies: FWD scale type bodies only

Tires: Gravity/Ride USGT tires and inserts, belted or non-belted

Race Length: 5min

Tamiya Mini:

Chassis: Tamiya M chassis or 3Racing MG chassis

Motor: Spec ORCA Q 2200KV (or Sky RC 2200KV equivalent), Stock Tamiya silvercan

Gearing: Kit gearing only. 5.8FDR (80/28) for 3Racing MG

ESC: Spec ORCA Q esc, Tamiya kit ESC, or ROAR approved ESC. Blinky mode only-no turbo/boost.

Battery: 2S hardcase. Max voltage 8.400V

Weight: 1200g min

Ride Height: 5mm min

Bodies: Any mini sized body

Tires: Any mini sized tires and wheels.

Race Length: 5min

Formula 1:

Chassis: Any 1/10 scale 190mm RWD F1 Chassis

Motor: ROAR approved 25.5T

Gearing: Open

ESC: ROAR approved, must be run in blinky mode only.

Battery: 2S hardcase. Max voltage 8.400V

Weight: 1050g min

Ride Height: 4mm min

Bodies: Any Formula 1 style body

Tires: F1 scale rubber tires only.

Race Length: 5min