

Name _____ Date _____ Track / City _____ Event _____

Front Suspension

Shock Stay:
 UM707(Std.)
 UMW739 Carbon
 UMW744 Wing
 UMW747 Wing Mount

Upper Spacer: _____ mm

4.8mm Ball Stud: Camber: _____ °
 UM128(Std.)
 UMW508 (+2mm High Mount)

AL. Steering Support:
 None
 UMW724

4.8mm Ball Stud:
 LA246 (-1mm Low Mount)
 97050M (Std.)

Ackerman Steer Spacer: _____ mm
 UMW701 Aluminum ST Plate
 UMW702 Aluminum Crank Arm

Toe: In Out _____ °

Tie Rod: _____

Sway Bar: _____ mm

Front Bulkhead Weight Placement:
 None
 Bulkhead Inside _____ oz / g
 On the skid plate _____ oz / g * 1oz=28g

4.8mm Ball Stud Spacer: _____ mm

AL. Steering Support:
 Out _____ mm
 In _____ mm

Wheel Hub:
 UM758(Std.)
 UM506
 UM506

Wheelbase: F: _____ mm R: _____ mm

Caster:
 25°
 30°

Caster Block: 0.5 0°
 1.0 2° IN (wide/Std)
 None 4° OUT (Narrow)

Caster Block Position: _____

Spacer: _____

Bump Steer Spacer: _____ mm

Knuckle:
 UM763(std.)
 UM714

Comments: _____

Rear Suspension

Shock Stay:
 Std.
 UMW740

Wing Stay:
 1
 2
 3

RR:
 1
 2
 3

Mid:
 1
 2

Sus Holder Spacer:
 F 0.5 1.0 None
 R 0.5 1.0 None

Anti-Squat: _____ °

Upper Spacer: _____ mm

4.8mm Ball Stud:
 UM129
 UMW508 (+2mm High Mount)
 97050M
 UM128(Std.)

Universal Swing Shaft:
 Type-B (UM519)
 Type-B2 (UM519-2)

Upper Spacer: _____ mm

Wheelbase: F: _____ mm R: _____ mm

Camber: _____ °

Sway Bar: _____ mm

Drive Hub:
 4mm (TFW113)
 4.5mm (LAW30GM)
 5.2mm (UMW523)
 6.2mm (UM773/Std.)

Rear Hub Carrier:
 0°Type-B (UM519)
 0°Type-B2 (UM519-2)
 0° Alu (UMW704-0)
 0.5°Alu (UMW704-05)
 1°Alu (UMW704-1)

Sus. Bush: In Out / Std. _____

Block: _____

Lower Sus. Holder:
 Plastic RF RF2L
 RF2
 Option UMW511GM (RF/Alu)

(Opt/Adjustable)
 UMW705(RF/Alu)
 UMW725(RF-MID/Bra)

(Opt/Adjustable)
 UMW706(RR-RWD)
 UMW707(RR-MID)

Toe: _____ °

Diff.:
 Gear Diff. # _____
 Ball Diff. Steel Aluminum

Shock

	Front	Rear
Shock Piston:	_____	_____
Shock Oil:	# _____	# _____
Shock Spring:	_____	_____
Limiters:	in _____ mm	in _____ mm
	out _____ mm	out _____ mm
Shock Length(A):	_____ mm	_____ mm
O-ring:	_____	_____
Shock Top:	<input type="checkbox"/> Alu.(UM719) <input type="checkbox"/> UM753-1B(Std.)	
Ball End:	Front: <input type="checkbox"/> S <input type="checkbox"/> M <input type="checkbox"/> L	
	Rear: <input type="checkbox"/> S <input type="checkbox"/> M <input type="checkbox"/> L	
Spring Sheet:	Front: <input type="checkbox"/> Std. <input type="checkbox"/> Low	
	Rear: <input type="checkbox"/> Std. <input type="checkbox"/> Low	

Battery Placement:

Foam:
 Front
 Rear
 None

Chassis:
 F _____ mm Ride Height: R _____ mm

Transmission

Rear Motor
 Mid-Ship 3 Gear
 Mid-Ship 4 Gear
 Mid-Ship Laydown
 Direct Gear
 Slipper Clutch

Battery Type

Straight
 Separate
 Short LCG

Track Condition

Smooth Sandy
 Bumpy Soft Dirt
 Low Traction Grass
 Med. Traction Blue Groove
 High Traction Clay
 Wet Dusty
 Dry Carpet

Rear Wing

UM767/Std.
 Step 3.0 - Straight
 Step 3.0 - Round
 Other _____

Lip: _____ mm

Tire

Tire: _____ Front _____ Rear _____ Traction Compound or comment: _____

Inserts: _____

Wheel: _____

Other

Servo: _____
 Motor: _____
 ESC: _____
 Pinion / Spur: _____

NOTES