Driver: Chris Goetz **Date:** 3/19/2006 Meeting: 2006 Roar Carpet Nationals Best Time: Qualified 4th, Finished 9th ○ Standard ● Carpet Ride Height ______5 ___mm Dil 80wt associated **⊚**OOO Anti-Roll Bar....none Spring IRS 32.5# Castor $O2^{\circ}$ **9**4° **O**6° Piston....2...3." Kick Up......O..........Anti-Dive.....O...... Length n/a mm Droop....2... Fill holes used Camber 1 degrees Centre Track Wishbone Short Mid/Short Mid/Long Olong Notes: Fill holes used 0 ● Carbon ○ Standard ○Standard ● Carpet Ride Height ______5 1 40wt associated Anti-Roll Bar none 0₀00 Spring. AE22# 0 Anti/Pro Squat. none Piston....2....3.... Toe-In (In) 2 degrees Length n/a mm 0 Roll Centre ______2 ___mm Fill holes used Camber ² degrees Fill holes used Wishbone Short Mid/Short Mid/Long OLong Spacer 2 MM \bigcirc O Notes: ● Carbon ○ Standard **●**Middle WheelBase 260 mm ORear Width Front....¹⁷⁹ MM. Rear....¹⁸⁰ MM. Bodyshell Parma Alpha Matar EA - Stock **Indoor** Differential Ostandard Olocked One-Way O Dutdoor Chassis 2.5 - Foam Spec ©Carpet Spring..... Top Deck 2.5 - Foam Spec Timing degrees **O**Concrete ESC Futaba MC800V2 **≧** ⊙Tarmac tooth Pinion Size..... Cells Hurricane 3800 tooth Spur Size..... Servo Futaba 9550 Receiver Futaba HRS 出 ● Tight **≥** • Open 42g weight added inside of Front Tyres. Parma Cyan - 55.5mm ● High servo, near belt. Rear Tyres Parma Magenta - 55.5mm **O**Medium Car was good, but not OLow Front Inserts..... perfect. Rear Inserts..... * Try bump steer shims with stiffer rear spring ● Smooth

** Try 2-hole pistons up front

w/ 50-60wt

Bumpy

Tyre Additive • Yes No Type Corally - JTG