

Cobra 4e SET UP



NAME Brad Rixman

RACE WC

DATE

DIFFERENTIAL OIL		
FRONT	CENTER	REAR
<u>500k CST</u>	<u>500k CST</u>	<u>40k . CST</u>

TRANSMISSION SET UP			
PINION	T	SPUR GEAR	T
FINAL DRIVE RATIO		ROLLOUT	mm
MOTOR	<u>Orion 2200</u>		TIMING
ROTOR			ARMATURE
ESC	<u>Nosram</u>		BATTERIES <u>5MC</u>
BRUSHLESS	PROGRAM	PUNCH	INITIAL BRAKE AUTO BRAKE

BODY - WING	
BODY	<u>Protoform Pfg.</u>
WING	

SHOCKS				
FRONT	SPRING	REAR		
SOFT		SOFT		
↓	<input type="checkbox"/> RED <input type="checkbox"/> PURPLE <input checked="" type="checkbox"/> YELLOW <input type="checkbox"/> WHITE <input type="checkbox"/> SILVER <input type="checkbox"/> BLACK	<input type="checkbox"/> RED <input checked="" type="checkbox"/> PURPLE <input type="checkbox"/> YELLOW <input type="checkbox"/> WHITE <input type="checkbox"/> SILVER <input type="checkbox"/> BLACK	↓	
HARD	<input type="checkbox"/> 1.000 <input type="checkbox"/> 0 <input type="checkbox"/> 6	OIL/CST <u>800</u> REBOUND % <u>0</u>	<input type="checkbox"/> 800 <input type="checkbox"/> 0	HARD
PISTON HOLES SIZE <input type="radio"/> OPEN <input checked="" type="radio"/> CLOSED				
<input type="checkbox"/> 1.1MM <input type="checkbox"/> 1.2MM <input checked="" type="checkbox"/> 1.3MM <input type="checkbox"/> 1.4MM OTHER			<input type="checkbox"/> 1.1MM <input type="checkbox"/> 1.2MM <input checked="" type="checkbox"/> 1.3MM <input type="checkbox"/> 1.4MM OTHER	

TYRES	
BRAND	<u>CRP</u>
TYPE	
INSERT	
WHEELS	

COMMENTS
 Good Set up for
 CRP 5's on Hot Track
 or 5 front / 3 rear
 night racing
 Using Blitz Shell

TRACK

STEERING BLOCK PLASTIC ALU

C-HUB ALU

WHEELHEX -2 mm

DOWNSTOP 4 mm

UPRIGHT: PLASTIC

DOWNSTOP 14 mm

CASTER 0

BRACE PLASTIC ALU

INSERT NR. 3 UP DOWN

INSERT NR. 3 UP DOWN

BRACE PLASTIC ALU

INSERT NR. 5 UP DOWN

STANDARD BRACKET OPTIONAL TYPE

STANDARD E OPTIONAL T

ANTI ROLLBAR 1.8mm 2.0mm 2.3mm 2.5mm 2.7mm

FRONT TOE - 0 +

SERVO SAVER SPRING STANDARD HARD

STEERING BAR OPT 1 OPT 2 OPT 3

WHEELBASE SHIM 0 1.25 2.5

ANTI ROLLBAR 1.8mm 2.0mm 2.3mm 2.5mm 2.7mm

FRONT CAMBER + 0 - i

ADJUST RIDE HEIGHT WITH COLLAR

RIDE HEIGHT 8 mm

ADJUST RIDE HEIGHT WITH COLLAR

RIDE HEIGHT