

# SET-UP SHEET

# XRAY RX8

RACE: **2011 Byron**

TRACK: \_\_\_\_\_

NAME: **Loran Whiting**

CITY / COUNTRY: \_\_\_\_\_

CONTACT: \_\_\_\_\_

DATE: **6/27/11** TEMPERATURE / °F or °C: \_\_\_\_\_ AIR: \_\_\_\_\_ TRACK: \_\_\_\_\_

QUALIFYING POSITION: \_\_\_\_\_ BEST LAPTIME /sec: \_\_\_\_\_ FINAL POSITION: \_\_\_\_\_ LAPS: \_\_\_\_\_ RACE LENGTH /minutes: \_\_\_\_\_

TRACK CONDITION:  SMOOTH  MEDIUM  BUMPY  
 TECHNICAL  MIXED  FAST

TRACTION:  LOW  MEDIUM  HIGH

**GEARING**

PINION 1ST: 16  17  18  2ND: 19  20  21  22

SPUR 1ST: 48  49  50  2ND: 45  46  47

PULLEY: 28  29  30  RATIO 1ST: \_\_\_\_\_ RATIO 2ND: \_\_\_\_\_

FRONT	SHOCKS	REAR
<b>Mugen White</b>	SPRING	<b>Mugen Gray</b>
<b>700</b>	OIL /cst	<b>600</b>
<b>25</b>	REBOUND %	<b>25</b>
	MEMBRANE	
<input type="checkbox"/> YES <input checked="" type="checkbox"/> NO	FOAM INSERTS	<input checked="" type="checkbox"/> YES <input type="checkbox"/> NO
<input type="checkbox"/> PLASTIC <input checked="" type="checkbox"/> ALU	SHOCK BODY	<input type="checkbox"/> PLASTIC <input checked="" type="checkbox"/> ALU
<input type="checkbox"/> YES <input checked="" type="checkbox"/> NO	ADJUSTABLE PISTONS	<input type="checkbox"/> YES <input checked="" type="checkbox"/> NO
	HOLE IN PISTON /mm	

OPENED  CLOSED

**HOLES IN PISTON**

FRONT	ANTI-ROLL BAR	REAR
<input checked="" type="checkbox"/> 0° <input type="checkbox"/> 30° <input type="checkbox"/> 45° <input type="checkbox"/> 60° <input type="checkbox"/> 90°	<input type="checkbox"/> 0° <input type="checkbox"/> 30° <input type="checkbox"/> 45° <input type="checkbox"/> 60° <input type="checkbox"/> 90°	<input type="checkbox"/> 0° <input type="checkbox"/> 30° <input type="checkbox"/> 45° <input type="checkbox"/> 60° <input type="checkbox"/> 90°
NO <input type="checkbox"/>	WIRE /mm	
0.7 <input type="checkbox"/>	<input checked="" type="checkbox"/> 1	

FRONT		TIRES	REAR	
LEFT	RIGHT		LEFT	RIGHT
		MANUFACTURER		
		SHORE / deg°		
		DIAMETER /mm		
		5 MIN. WEAR /mm		
		RUBBER TIRES		

**ENGINE**

TYPE: \_\_\_\_\_

CARB. DIA /mm: \_\_\_\_\_ HEAD SHIM /mm: \_\_\_\_\_ PLUG: \_\_\_\_\_

MUFFLER: \_\_\_\_\_ FUEL: \_\_\_\_\_

**CLUTCH / BRAKE**

FLYWHEEL:  STANDARD  OTHER

CLUTCH FLYWEIGHTS:  STANDARD  OTHER

CLUTCH SHOE: \_\_\_\_\_ CLUTCH SPRING:  STANDARD

CLEARANCE /mm: \_\_\_\_\_ ADJ. NUT /mm: \_\_\_\_\_

BRAKE PAD:  STANDARD  OTHER

BRAKE SETTING %: \_\_\_\_\_

**BODY**

WING HEIGHT: \_\_\_\_\_

WING POSITION: \_\_\_\_\_

Drilled 1mm hole in shock top on front shocks  
 No foam in front.

COMMENTS

