



Presented by

Tri-Cities RC Summer Series Slash SPEC CLASS RULES!

This Class is basically for the Ready-To-Race Version of the vehicle as shipped by Traxxas. The idea is to limit the amount of hop-ups or modifications to the factory supplied vehicle to control costs.

Body: All trucks must use the factory Traxxas body, or Pro-Line Slash specific models.

Chassis: No modifications may be made to the chassis system. Vehicle must be raced in its stock form. Original Traxxas Replacement parts, as supplied on original model 5805 truck kit, only for damaged/worn parts.

Suspension: Both the front & the rear suspension systems must remain in stock form. Original Traxxas parts only. No aftermarket/Hop up replacement components may be installed. The *Exception* is the use of RPM rear hub carriers are allowed.

Legal Tuning Parts: Original 5805 Traxxas Kit Shock white springs may be used. Shock Cap may be replaced with Alum Shock Cap #2667
Original Traxxas Turnbuckles maybe used 3139X, 3139A, 3737, 3737A

Steering: No modifications may be made to the steering system. Original kit parts only.

Bearings: Any manufacturer Bearing may be used.

Electronics: Original RTR Kit electronics Speed Control (XL-5) & Servo (2075) only. You may install any different receiver if you so choose.

Motor: This class is restricted to a stock Traxxas Titan 12T R/C motor.

Battery: This class is limited to any 7.2 volt "NiCad", "NiMh" made up of 6 "sub C" size cells only or Lipo 7.4 volt Battery pack made up of 2 cells only **LIMIT of 40C and 5500 mah (If you run larger than 30C you will be required to add an additional 2oz (1/8 lb) of weight).**

Wheels: Original Traxxas Slash 2.2" wheel (Pro-Line and other aftermarket wheels are NOT allowed)

Tires: Original Traxxas 2.2" Slash Tire (Pro-Line and other aftermarket tires are NOT allowed)

Drive Line: Only the original Traxxas Drive Train may be used. No aftermarket or Hop-up replacement drive components may be installed.

Any of the 3 Traxxas spur gears (4683, 4686, or 8690) are permitted. Any pinion gear that mounts without modifications needed may be used. Ball Differential is NOT permitted in the Spec Class.

Weight: Truck must weigh no less than **5.5 pounds Ready to Race this will be enforced.**