

NOVAROSSİ TURBO GLOW PLUGS

Turbo Glow Plugs were designed to give more performance to an engine, for the following reasons:

_It forms an uninterrupted combustion chamber.

_The advantage of better heat transfer or heat dissipation, and a leak proof seal, generated by the conical seat of the plug.

_Greater choice of thermal ranges, that allow for more precise tuning according to variations in weather conditions (temperature, humidity, altitude, barometric pressure, etc.).

The numbers and characters on the plugs, are the product number, wire thickness, and thermal range of the plug's body. Example: The Novarossi C6TG (F) or (C)

§ Product: C (Conical)

§ Wire Thickness: 6

§ Plug Type: T (Turbo)

§ Plated: G (Gold)

§ Thermal Range: F (Fredda = Cold) C (Calda = Hot) H (Hot = same as C)

The plugs with cold thermal range F (Fredda), have a body with thinner walls and shorter body, so they dissipate heat better and faster to the engine head. The plugs with hot thermal range C (Calda), have a body with thicker walls and longer body, so they contain their heat better and dissipate it slower to the head. The number of threads is the same on both types of plugs.

How to select the proper plug:

_When the ambient temperature is high, we have to use a plug with thicker wire.

_With higher compression, we have to use a plug with thicker wire.

_Humidity determines if we use a Cold (F) thermal range, or Hot (C) thermal range.

_With high humidity percentage we should use a Hot (C) thermal range plug.

_If we have high temperature and high humidity, we should use a plug with thick wire and a Hot(C) thermal range.

The best instrument to determine which Turbo Plug to use, is those table digital weather stations, that have Temperature, Humidity, and some also Barometric Pressure on them. That is the key to success or failure tuning engines with Turbo Glow Plugs, because they are so sensitive to weather variations that is unbelievable.

Following is a selection chart for Novarossi Turbo Glow Plugs

Type	Thermal Range	Nitro%	Air Temp.C°	Humidity
C5TGC Hot/hot wire	10-20	0-10		70-100
C6TGC Hot/average wire		10-20	10-16	70-100
C7TGC Hot/cold wire		20-30	16-25	70-100
C8TGC Hot/ultra cold wire		30-up	25-up	70-100
C5TGF Cold/hot wire		10-20	0-10	40-70
C6TGF Cold/average wire		10-20	10-15	40-70
C7TGF Cold/cold wire		20-30	16-25	40-70
C8TGF Cold/ultra cold wire		30-up	25-up	40-70