TAMIYA R/C 16th ASIA CUP SINGAPORE CHAMPIONSHIP 2013

CAR REGULATIONS



1. Cars eligible for qualification: All types of Tamiya 4WD Touring Chassis (Including TRF Series).

- 2. Only #54132 Tamiya Sensorless Brushless motor 12T is permitted to be used. Only TBLE01 Tamiya Brushless ESC can be used.
- 3. Original Tamiya rubber tires only.
- 4. Any Tamiya Hop-Up Option and spare part is allowed as long as it is used in the way it designed, and on the vehicle it was designed for.
- 5. All Tamiya car bodies must be painted.
- 6. Any attempt to modify or to influence the ability of the motor is not allowed. However, wires of speed controller can be soldered to motor.
- 7. Any attempt to modify or to influence the ability of the E.S.C is not allowed (inclusive of adding additional capacitors and other E.S.C influencing device.) Only battery plugs can be changed.
- 8. Battery wires can be modified at the bottom of connecter to accept other type of speed controller connecters. Wire length must exceed 3cm.
- 9. Minimum weight of car ready to run is to be 1,450grams.
- 10. Clearance under main chassis parts must exceed 5mm before the race.
- 11. Any form of driving aid is not allowed to be use. - eg. Gyro, Active Steering Assist Unit.



Issued on DEC 18, 2012